

0.8m Single Rail Reject Conveyor (Model:PTB-F460)

一、Features		
1	Green flat imported anti-static transmission belt, durable, simple maintenance	
2	The sheet metal weights the structure, the whole machine is stable, and it is not easy to shift	
3	PLC control system, universal SMEMA communication mode	
4	HIM simple and easy to understand	
5	Multiple electrical distribution circuit protection, safe and reliable	
二、Specifications & Technical Parameters		
1	Transmission height	900±20mm
2	Transmission direction	L→R
3	Circuit board effective size	80(L)*50(W)-510(L)*460(W)mm
4	Rack	One-piece design, steel plate bending welding, surface powder spray production
5	Layer spacing	The layer distance is 25mm, total 5 layers
6	Conveyor belts	1.0mm anti-static belt
7	Transmission speed	0.5M/min
8	Width adjustment method	Manual adjustment
9	Dimensions (L*W*H)	800*780*900mm
10	Transmission motor	Qinglan 57 stepper motor
11	NG board lifting motor	Qinglan 57 stepper motor
12	Inductor	German Leuze
13	PLC	Japan Panasonic
14	I/O interface	Standard SMEMA interface on the front and back
15	Electronic control	Omron relays
16	power supply	AC 220V,50Hz
17	Weight(Kg)	120Kg



Note: The picture is for reference only, and the specific specifications and models are subject to the text content.