

Automatic Buffer Stocker (Model:ZCL-3BM)

一、Features					
1	Man-machine interface control operation, simple and convenient				
2	PLC control system, multiple electrical circuit protection design, safe and stable				
3	There are 30 pitches in the staging area for boarding				
4	Comprehensive multiple functions, first in-first-out, first-in-last-out, straight-through				
5	Servo positioning system, high positioning accuracy, fast lifting speed, high production efficiency				
6	Standard SMEMA signal communication method				
二、Specifications & Technical Parameters					
1	<table border="1"> <tr> <td>Description</td> <td> It can be used as a buffer between SMT machines. It can be used to automatically collect AOI inspection NG/OK boards into different layer segments. </td> </tr> </table>	Description	It can be used as a buffer between SMT machines. It can be used to automatically collect AOI inspection NG/OK boards into different layer segments.		
Description	It can be used as a buffer between SMT machines. It can be used to automatically collect AOI inspection NG/OK boards into different layer segments.				
2	<table border="1"> <tr> <td>Board capacity</td> <td>30 pcs or user specified</td> </tr> <tr> <td>Maximum load</td> <td>1.5 kg/PCB</td> </tr> </table>	Board capacity	30 pcs or user specified	Maximum load	1.5 kg/PCB
Board capacity	30 pcs or user specified				
Maximum load	1.5 kg/PCB				
3	Cycle time About 12 seconds				
4	Step selection 30、 60 mm or user specified				
5	Power supply & Electrical load 220V AC, single phase Max 850 VA				
6	Board thickness Minimum 0.6 mm				
9	Circuit board effective size(mm) 80(L)*50(W)~510(L)*460(W)mm				
10	Transmission direction L → R; or R →L (Optional)				
11	Transmission height 900±20mm				
12	Dimensions (L*W*H) L600*W1200*H1760mm				
13	Weight (kg) 155kg				



Note: The picture is for reference only, and the specific specifications and models are subject to the text content.