

Automatic Cooling Buffer Stocker With Platform (Model:ZCLC-3XL-S)

一、Features			
1	Man-machine interface control operation, simple and convenient		
2	PLC control system, multiple electrical circuit protection design, safe and stable		
3	There are 20 pitches in the staging area for boarding		
4	Comprehensive multiple functions, first-in-first-out, pass-through, NG/OK		
5	Servo positioning system, high positioning accuracy, fast lifting speed, high production efficiency		
6	Standard SMEMA signal communication method		
7	The innovative structure makes the board surface fully exposed to cold air and cools down quickly		
二、Specifications & Technical Parameters			
1	<table border="1"> <tr> <td>Description</td> <td> It can be used as a buffer between SMT machines. It can be used for rapid cooling of PCBs after reflow soldering or high-temperature equipment. </td> </tr> </table>	Description	It can be used as a buffer between SMT machines. It can be used for rapid cooling of PCBs after reflow soldering or high-temperature equipment.
Description	It can be used as a buffer between SMT machines. It can be used for rapid cooling of PCBs after reflow soldering or high-temperature equipment.		
2	Board capacity	20pcs, or user specified	
3	Maximum load	1.5 kg/PCB	
4	Cycle time	About 12 seconds	
5	Step selection	30、 60 mm or user specified	
6	Power supply & Electrical load	220V AC, single phase Max 850 VA	
7	Board thickness	Minimum 0.6 mm	
8	Circuit board effective size(mm)	80(L)*50(W)~510(L)*460(W)mm	
9	Transmission direction	L → R; or R →L (Optional)	
10	Transmission height	900±20mm	
11	Dimensions (L*W*H)	L1600*W1200*H1760mm	
12	Weight (kg)	300kg	



Note: The picture is for reference only, and the specific specifications and models are subject to the text content.