

Automatic NG/OK Buffer Stocker (Model:ZCLA-3L)

一、Features		
1	Man-machine interface control operation, simple and convenient	
2	PLC control system, multiple electrical circuit protection design, safe and stable	
3	There are 25 pitches in the staging area for boarding	
4	Comprehensive multiple functions, first-in-first-out, pass-through, NG/OK	
5	Servo positioning system, high positioning accuracy, fast lifting speed, high production efficiency	
6	Standard SMEMA signal communication method	
二、Specifications & Technical Parameters		
1	Description	It can be used for NG screening after SMT inspection equipment. It can be used to automatically collect AOI inspection NG/OK boards into different magazine.
2	Board capacity	25pcs, the number of NG/OK storage boards can be selected for multiple purposes
	Maximum load	1.5 kg/PCB
3	Cycle time	About 12 seconds
4	Step selection	30、 60 mm or user specified
5	Power supply & Electrical load	220V AC, single phase Max 850 VA
6	Board thickness	Minimum 0.6 mm
9	Circuit board effective size(mm)	80(L)*50(W)~400(L)*350(W)mm
10	Transmission direction	L → R; or R →L (Optional)
11	Transmission height	900±20mm
12	Dimensions (L*W*H)	L1000*W1100*H1760mm
13	Weight (kg)	240kg



Note: The picture is for reference only, and the specific specifications and models are subject to the text content.