

Heavy NG/OK Buffer Stocker (Model:ZLL-650)

一、Features			
1	HIM operation system and function switching, simple and easier to understand		
2	PLC control system, multiple electrical circuit protection design, safe and stable		
3	Suitable for heavy or large product production		
4	Comprehensive multiple functions, first-in-first-out, pass-through, NG/OK		
5	Servo positioning system, high positioning accuracy, fast lifting speed, high production efficiency		
6	Standard SMEMA signal communication method		
二、Specifications & Technical Parameters			
1	<table border="1"> <tr> <td>Description</td> <td> It can be used for NG screening after SMT inspection equipment. It can be used to automatically collect AOI inspection NG/OK boards into different layer. </td> </tr> </table>	Description	It can be used for NG screening after SMT inspection equipment. It can be used to automatically collect AOI inspection NG/OK boards into different layer.
Description	It can be used for NG screening after SMT inspection equipment. It can be used to automatically collect AOI inspection NG/OK boards into different layer.		
2	<table border="1"> <tr> <td>Power supply & Electrical load</td> <td>220V AC, single phase Max 2200 VA</td> </tr> </table>	Power supply & Electrical load	220V AC, single phase Max 2200 VA
Power supply & Electrical load	220V AC, single phase Max 2200 VA		
3	<table border="1"> <tr> <td>Board thickness</td> <td>Minimum 0.6 mm</td> </tr> </table>	Board thickness	Minimum 0.6 mm
Board thickness	Minimum 0.6 mm		
4	<table border="1"> <tr> <td>Transmission height</td> <td>900±20mm</td> </tr> </table>	Transmission height	900±20mm
Transmission height	900±20mm		
5	<table border="1"> <tr> <td>Circuit board effective size(mm)</td> <td>80(L)*50(W)~700(L)*650(W)mm</td> </tr> </table>	Circuit board effective size(mm)	80(L)*50(W)~700(L)*650(W)mm
Circuit board effective size(mm)	80(L)*50(W)~700(L)*650(W)mm		
6	<table border="1"> <tr> <td>Air pressure</td> <td>4 ~ 6bar</td> </tr> </table>	Air pressure	4 ~ 6bar
Air pressure	4 ~ 6bar		
7	<table border="1"> <tr> <td>Motor power</td> <td>25W</td> </tr> </table>	Motor power	25W
Motor power	25W		
8	<table border="1"> <tr> <td>layer spacing</td> <td>60mm</td> </tr> </table>	layer spacing	60mm
layer spacing	60mm		
9	<table border="1"> <tr> <td>Maximum weight of veneer storage plate</td> <td>10kg</td> </tr> </table>	Maximum weight of veneer storage plate	10kg
Maximum weight of veneer storage plate	10kg		
10	<table border="1"> <tr> <td>Transmission direction</td> <td>L → R or R →L (Optional)</td> </tr> </table>	Transmission direction	L → R or R →L (Optional)
Transmission direction	L → R or R →L (Optional)		
11	<table border="1"> <tr> <td>Dimensions (L*W*H)</td> <td>L1600*W1300*H1760mm</td> </tr> </table>	Dimensions (L*W*H)	L1600*W1300*H1760mm
Dimensions (L*W*H)	L1600*W1300*H1760mm		
12	<table border="1"> <tr> <td>Weight (kg)</td> <td>300kg</td> </tr> </table>	Weight (kg)	300kg
Weight (kg)	300kg		



Note: The picture is for reference only, and the specific specifications and models are subject to the text content.